

1360 Livingstone Road • Hudson, Wisconsin 54016 (715) 386-2930

BUILDERS OF THE ORIGINAL EMPIRE BUCKET

HYDRAULIC & STATIONARY THUMBS



SPECIFICALLY
DESIGNED
TO MATCH YOUR
BUCKET TIP RADIUS
AND TOOTH
SPACING TO
ACCOMMODATE
EXACT PICKING AND
SORTING NEEDS
FOR ANY JOB.







All T1 and HX400 construction.

Replaceable, bronze bushing for extended wear life.

Hinge pin rotates with bucket to eliminate wear to bucket bores.

Each thumb is specifically designed for the bucket.

Thumbs are designed for convenient stow position in mounting bracket.

Empire Bucket will custom design our thumb to match your specific need!

Special picking or sorting needs? Empire will design a thumb to match your bucket width, tip radius and tooth spacing!

Empire's Hydraulic Thumbs will give you a strong, positive grip on your load and will quickly stow when needed - out of your work zone.

Our custom design provides you with the largest possible working range!

Empire's Mechanical Link Thumbs are a low-cost option for an excavator that doesn't have stick hydraulics, or for occasional use.

Specifications for Typical Empire Thumbs

| Excavator Weight Class | Hydraulic Thumbs | | | | Mechanical Link Thumbs | | | |
|---------------------------|---|-----------|--------------------------|-----------|------------------------|-----------|---------------------|-----------|
| | 2 Tine Standard Width | | Wide Thumbs -3 or 4 Tine | | 2 Tine Standard | | Wide Thumbs -3 or 4 | |
| | Std Mount | w/Coupler | Std Mount | w/Coupler | Std Mount | w/Coupler | Std Mount | w/Coupler |
| 14,000 - 21,000# | Typical Weight: Hydraulic Cylinder Size: | | 500# 4" x 24" | | 400# | 420# | 450# | |
| 21,001 - 28,000# | Typical Weight: Hydraulic Cylinder Size: | | 600# 4.5" x 30" | | 575# | 600# | 750# | |
| 28,001 - 36,000# | Typical Weight: Hydraulic Cylinder Size: | | 800# 4.5" x 30" | | 650# | 700# | 900# | |
| 36,001 - 48,000# | Typical Weight: Hydraulic Cylinder Size: | | 1000# 5" x 36" | | 900# | 950# | 1150# | |
| 48,001 - 60,000# | Typical Weight: Hydraulic Cylinder Size: | | 1250# 5" x 36" | | 1100# | 1150# | 1400# | |
| 60,001 - 75,000# | Typical Weight: Hydraulic Cylinder Size: | | 1500# 6" x 42" | | 1250# | 1350# | 1600# | |
| 75,001 - 90,000# | Typical Weight: Hydraulic Cylinder Size: | | 2000# 6" x 42" | | 1800# | 2000# | 2000# | |
| 90,001 - 125,000# | Typical Weight: Hydraulic Cylinder Size: | | 3000# 6" x 48" | | 2650# | 2900# | 3000# | |

Empire Thumbs are made using high grade composite materials T-1 and Hardox and typically include greasable, replaceable bronze bushings for long wear life.

Hinge pin rotates with the bucket, reducing wear to bucket bores.

Mounting Information

Empire Thumbs are supplied with mounting pins, mechanical link or hydraulic cylinder, and a mounting pad that must be welded to the excavator stick.

Hydraulic thumbs require a control valve and hydraulic lines that include a relief valve in the thumb circuit.

